DRUTEX
WINDOWS DOORS SHUTTERS GATES

Official Partner of

FC BAYERN MÜNCHEN



D-GATE
ROLLER GARAGE EVO 77

DRUTEX
WINDOWS DOORS SHUTTERS GATES

D-GATE ROLLER GARAGE DOOR EVO 77

D-Gate roller garage doors are a practical and modern solution that performs reliably in all weather conditions. Thanks to their robust construction and durable components, they provide everyday comfort, safety, and reliable operation. Their elegant appearance and wide range of colors make it easy to match the garage door to the style of any building.





SPECIFICATIONS

somfy CAME

Maximum width	
90 mm aluminum guides	**450 cm**
90 mm aluminum guides + storm hooks	**640 cm**
Maximum height	
Aluminum box 250	**200 cm**
Aluminum box 300	**280 cm**
Aluminum box 300 for widths above 450 cm	**260 cm**
Aluminum box 350	**390 cm**
Aluminum box 400	**510 cm**
Maximum door area	**22 m2**
Insulated aluminum profile 640 cm, Steel 350 cm	**77**
Profile EasyLook	**EasyLook 77**
Ventilation profile	**WENT 77**
Profile height	**77 mm**
Profile thickness	**18 mm**
Curtain weight	**4,8 kg/m2**
Motors (available from a total width of 100 cm)*	**KraftMaster**

Minimum door area: 6 m². Doors with an area below 6 m² are calculated as 6 m².

* doors below 100 cm in width are sold as a gate element without the possibility of installing a motor.

AVAILABLE BOXES, PROFILES AND GUIDES



















COLORS

- white
- ultra white* RAL 9016
- grey RAL 7038
- silver RAL 9006
- anthracite RAL 7016
- ivory* RAL 1015
- cream white* RAL 9001
- beige
- brown RAL 8014
- dark brown RAL 8019
- black RAL 9005
- red* RAL 3003
- burgundy* RAL 3005
- chartwell green *
- green* RAL 6005
- fir green* RAL 6009
- duck egg blue*
- blue* RAL 5005
- steel blue* RAL 5011
- slate grey* RAL 7015
- golden oak*
- walnut*, **
- irish oak* (curtain only)
- dark wood*(armor only)
- pearl anthracite grey*

Available elements in any RAL color: box, guides, bottom rail.
The colors shown are for illustrative purposes only and may slightly differ from the actual colors.
*Colors marked with an asterisk are subject to an additional charge: curtain with bottom rail 10%, box 10%, guides 5%.
**Available only with 300 and 350 boxes.

KRAFTMASTER CONTROL SYSTEMS



Control Unit KraftMaster
WiFi SmartLine,
+ 2 four-channel remote
controls



Control Unit
KraftMaster PROLINE
+ 2 four-channel remote
controls



ECOLINE/PROLINE
4-channel remote
control



Fotocell
PROLINE

SOMFY CONTROL SYSTEMS



Control Unit
ROLLIXO OPTIMO RTS
+ 2 remote controls



Keygo 4 rts 4-channel
remote control for
key ring



Warning light
with antenna



Wireless code keypad
DIGIPAD RTS

SWITCHES AND CONTROLLERS

Key switches directional



Recessed



Surface-mounted

Key switches impulse



Recessed



Surface-mounted

Push-button directional



Recessed



Surface-mounted

Push-button impulse



Recessed



Surface-mounted



Wireless wall switch



Dual do controller for 2 switches



Universal controller



Driver ClickME ShutterBox by BleBox



Driver ClickME ShutterBox by BleBox

EXTRAS



Inertial brake *



Cardan joint 90°





Safety lock for crank hole



Optical strip wired/wireless



Cranks for emergency opening



Ventilation profile



Easylook profile with transparent strip



Wired/Wireless Photocells

* accessories included in standard equipment

Quality

The latest technology, the best materials, production control at every stage, and our own research laboratories guarantee the highest quality.

Safety

Garage doors are equipped with reliable hardware and locks that enhance user safety.

Service

Professional and prompt service is a hallmark of DRUTEX, which has been setting the standard in pre- and after-sales customer support for years.

Smart Home

Smart control of doors, windows, roller shutters, external venetian blinds, insect screens, gates, wickets, and lighting via smartphone.

DRUTEX
WINDOWS DOORS SHUTTERS GATES

Official Partner of FC Bayern

ul. Leszka Gierszewskiego 1, 77-100 Bytów
+48 59 822 91 01

SINCE 1985

The information presented in this promotional material is for informational and illustrative purposes only.The product specification should be verified against the technical data provided by the manufacturer.